



400 Hz Solid-State Converter

400 Hz Solid-State Converter—120–180 kVA



400 Hz Solid-State Converter—180 kVA

THE ADVANTAGES

- NFPA 70 Article 500 Class 1 Div. 2 compliant with 18" Floor Stand
- Trailer mounted units are compliant with SAE AS8090 Type 1 Class 2 requirements.
- Easy-to-read Digital Information Display
- Modular design allows for ease of maintenance
- BIT: Digital diagnostics aid troubleshooting

Our 400Hz Frequency Converter provides a complete fully integrated and tested system which is ready to install as delivered. Front access for all service and maintenance functions. 30-40% space and weight savings compared with competitive products. The compact light weight adaptable design allows flexible installation options. It can be floor mounted, overhead mounted or mounted on a trailer or castors.

ITW MILITARY GSE

ITW Military GSE is an Illinois Tool Works (ITW) company. ITW is a diverse Fortune 200 company with over 850 operating divisions in 49 countries worldwide. ITW Military GSE is a world-class engineering-based company headquartered in Palmetto, Florida. We specialize in the design, manufacture, and world wide service of Military Aircraft Ground Support Equipment providing GSE to U.S. and foreign military programs since 1972.



PERFORMANCE FEATURES

Proven design:

- Meets and Exceeds MIL-STD-704F requirements
- Total harmonic content <2%
- Up to 4 outputs available
- Soft Start feature eliminates in-rush current

Model	Input Power	Output Power	Depth	Width	Height	Weight
180 kVA 400 Hz SS Converter	400/480 VAC, 50/60 Hz	115/200 VAC, 400 Hz, 180 kVA	36" (914 mm)	60" (1524 mm)	81" (2057 mm)	1,958 lbs (888 kg)

FROM DESIGN TO DEPLOYMENT

400 Hz Solid-State Converter—120–180 kVA Unit Specifications

OUTPUT

- Power: 180 kVA @ 0.8pf Lag
- 115/200 V - WYE, ABC-N
- Frequency: 400 Hz \pm 0.1%
- Power factor: 0.5 lag to 0.9 lead
- Voltage regulation: <1%
- Transient performance exceeds MIL-STD-704F
- Crest factor: 1.414 \pm 3%
- Overload Rating:
 - 110% for 60 minutes
 - 125% for 5 minutes
 - 150% for 2 minutes
 - 200% for 20 seconds
 - 300% for 6 seconds

EFFICIENCY

- 12 pulse Front End
- Overall efficiency:
>0,90 at 90-180 kVA load
- No load loss: <2 kW

PROTECTION

- No break power transfer
- Over/under voltage: Input and Output
- Overload
- Short circuit
- High temperature
- Internal system error

ENVIRONMENTAL

- Operating temperature: -40°C to +55°C
- Relative humidity 0-95%
- Airborne Noise <65 dba @1m - typically 60 dba

MISCELLANEOUS

- MTBF (Proven): 100,000 hours
- MTTR: max. 20 minutes
- Rated current: 190 A \pm 15%

STANDARDS

- MIL-STD-704F Aircraft electric power characteristics
- MIL-STD-1399-300 Interface Standard for Shipboard Systems

- MIL-STD-1472F Human Engineering
- UFGS-26 35 43 Unified Guide Specification
- DFS 400 Specification for 400hz Aircraft Power
- BS 2G 219 General Requirements for Ground Support Equipment
- UL & CE Listed

OPTIONS

- External Emergency Stop
- Remote Control Box
- 6 pulse Front End
- 18" Floor Stand
- Trailer per SAE AS8090
- Door/Panel Interlock
- Loss of Neutral Detection
- Portable Service Lamp
- 400Vac/50hz Input
- Up to 4 outputs available
- EMI Package

Specifications subject to change without notice.

The 400 Hz–180 kVA Converter is compatible with these aircraft and others:



Headquarters & Factory: 11001 US Hwy. 41 North, Palmetto, FL 34221 U.S.A.
Phone: 941.721.1003; 941.721.1006 • Fax: 941.723.3582; 941.531.5876
E-mail: sales@itwmilitarygse.com • www.itwmilitarygse.com

Updated 8/30/09

F R O M D E S I G N T O D E P L O Y M E N T